

DIGIFORT - Digital Printed Wallcovering

Product datasheet

Product description : Non-woven backed vinyl wallcovering Bio-Pruf™ treated

Composition		Dimensions	Test method
Total weight	20	Oz/ly	ISO 2286-2
Roll width	1300	mm	
Roll length	50	meter	
Internal core diameter	76	mm	
Packaging	Kraft paper		

*Vinyl base coating with specially formulated acrylic topcoating with exclusive inkjet receptive properties.

Product features prior to printing

Suitable printing inks	Latex, Eco-solvent, Solvent, UV-curable	
Resistant to	Soap; detergents; alcohol; ammonia; alkali; diluted acids	
Non resistant to	Solvents like ketones; esters; aromatic hydrocarbons	
Washability	Extra scrubbable - EN 259-1 / EN12956	
Light fastness	≥ 7 International Woolscale - BS EN 20105 / ISO EN 105-B02	
Bio-Pruf™	Bio-Pruf™ treated to resist the growth of mold/mildew and odor causing microbes	
FSC™	FSC™ certified: FSC-C141806	
Reach	Reach compliant according to EU regulation 1907/2006EC	
Made in EU	CE Compliant – according to EN 15102:2007 + A1:2011	
	Details see Declaration of Performance 11	

Fire safety

Euroclass	B-s1-d0	EN13501-1
Germany	B1	DIN4102-1
ASTM	Class A	E84-15a

Application instruction

Adhesives	Heavy duty wallcovering adhesive McBond /McBond Plus similar PVA substitute
-----------	---

Product sheet last revised: 01-02-2020